



B19



THE kpx LIGHT INTEGRATOR (B19)

- Single channel digital integrator. Reading light units emitted from a light source, compensating automatically for tube deterioration digital light integrator
- Resetting facility
- Start / cancel buttons
- Fused system

Electrics: 220/240v, 50/60 Hz, 2 amps

A20



THE kpx 'PRINTASCREEN' TOTALLY ENCLOSED EXPOSURE SYSTEM (A20)

- Metal halide light sources, 2 Kw, 3/5 Kw, 4/6 Kw available
- Exposure by self compensating digital light integrator
- High vacuum pressure units available (option)
- Glass cooling fans
- Stencil safe lights & retouching lights
- Highly flexible vacuum blanket suitable for direct & indirect stencil systems
- Ultra fast vacuum exhaust system using all four sides of the blanket frame

MODEL	Max. Frame Size	Light Source Power	Electrics	Overall Dims	Height
I	40" x 28" 101cm x 71cm	2 Kw	220/240v 50/60 Hz	49" x 42" 124cm x 106cm	48" 122cm
II	50" x 40" 127cm x 101cm	2 Kw	220/240v 50/60 Hz	59" x 53" 150cm x 136cm	48" 122cm
II-I	50" x 40" 127cm x 101cm	3/5 Kw	380/415v 50/60 Hz	59" x 53" 150cm x 136cm	48" 122cm
III	65" x 55" 165cm x 139cm	2 Kw	220/240v 50/60 Hz	74" x 68" 188cm x 174cm	51" 130cm
III-I	65" x 55" 165cm x 139cm	3/5 Kw	380/415v 50/60 Hz	74" x 68" 188cm x 174cm	51" 130cm
III-2	65" x 55" 165cm x 139cm	4/6 Kw	380/415v 50/60 Hz	74" x 68" 188cm x 174cm	51" 130cm